

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name 314

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Water based, acrylic, satin enamel for interiors and exteriors. Professional and Commercial Use.

Uses advised against Uses other than those indicated

#### 1.3. Details of the supplier of the safety data sheet

Name OIKOS S.P.A. A SOCIO UNICO  
Full address Via Cherubini 2  
District and Country 47043 Gatteo Mare (FC)  
Italia  
Tel. 0547 681412  
Fax 0547 681430  
e-mail address of the competent person responsible for the Safety Data Sheet certificazioniprodotti@oikos-group.it

#### 1.4. Emergency telephone number

For urgent inquiries refer to NHS National Health Service 111

OIKOS S.P.A. a socio unico Company emergency number: 0547 681412  
Technical support - Monday to Friday from 8.00-13.00; 13:30 to 16:30

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210**  
**EUH208**

Safety data sheet available on request.  
Contains: 2-methyl-2H-isothiazol-3-one  
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and  
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)  
1,2-benzisothiazol-3(2H)-one  
May produce an allergic reaction.

Precautionary statements: --

VOC (Directive 2004/42/EC) :

## SECTION 2. Hazards identification ... / &gt;&gt;

Interior / exterior trim varnishes and woodstains, including opaque woodstains.  
VOC given in g/litre of product in a ready-to-use condition : 95,00  
Limit value: 130,00

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

## 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>(2-methoxymethylethoxy)propanol</b>		
INDEX	$1,5 \leq x < 2,5$	Substance with a community workplace exposure limit.
EC	252-104-2	
CAS	34590-94-8	
REACH Reg.	01-2119450011-60	
<b>1,2-benzisothiazol-3(2H)-one</b>		
INDEX	$0,029 \leq x < 0,035$	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	220-120-9	Skin Sens. 1 H317: $\geq 0,05\%$
CAS	2634-33-5	LD50 Oral: >490 mg/kg bw
REACH Reg.	01-2120761540-60	
<b>Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</b>		
INDEX	$0,00015 \leq x < 0,0011$	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100
EC	611-341-5	Skin Corr. 1C H314: $\geq 0,6\%$ , Skin Irrit. 2 H315: $\geq 0,06\%$ , Skin Sens. 1A H317: $\geq 0,0015\%$ , Eye Dam. 1 H318: $\geq 0,6\%$ , Eye Irrit. 2 H319: $\geq 0,06\%$
CAS	55965-84-9	LD50 Oral: >64 mg/kg bw, STA Dermal: 50,001 mg/kg, STA Inhalation vapours: 0,501 mg/l
REACH Reg.	01-2120764691-48	
<b>2-methyl-2H-isothiazol-3-one</b>		
INDEX	$0,00015 \leq x < 0,0011$	Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, EUH071
EC	220-239-6	Skin Sens. 1A H317: $\geq 0,0015\%$
CAS	2682-20-4	STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, LC50 Inhalation mists/powders: 0,1 mg/l/4h
REACH Reg.	01-2120764690-50	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

## 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.


SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

## 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

	<div>OIKOS S.P.A. A SOCIO UNICO</div> <div>314</div>	<div>Revision nr.4</div> <div>Dated 12/03/2024</div> <div>Printed on 12/03/2024</div> <div>Page n. 3 / 12</div> <div>Replaced revision:3 (Dated 02/09/2022)</div> <div>EN</div>
SECTION 4. First aid measures ... / >>		
<div>4.3. Indication of any immediate medical attention and special treatment needed</div> <div>Information not available</div>		
SECTION 5. Firefighting measures		
<div>5.1. Extinguishing media</div> <div>SUITABLE EXTINGUISHING EQUIPMENT</div> <div>The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.</div> <div>UNSUITABLE EXTINGUISHING EQUIPMENT</div> <div>None in particular.</div> <div>5.2. Special hazards arising from the substance or mixture</div> <div>HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE</div> <div>Do not breathe combustion products.</div> <div>5.3. Advice for firefighters</div> <div>GENERAL INFORMATION</div> <div>Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.</div> <div>SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS</div> <div>Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).</div>		
SECTION 6. Accidental release measures		
<div>6.1. Personal precautions, protective equipment and emergency procedures</div> <div>Block the leakage if there is no hazard.</div> <div>Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.</div> <div>6.2. Environmental precautions</div> <div>The product must not penetrate into the sewer system or come into contact with surface water or ground water.</div> <div>6.3. Methods and material for containment and cleaning up</div> <div>Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.</div> <div>Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.</div> <div>6.4. Reference to other sections</div> <div>Any information on personal protection and disposal is given in sections 8 and 13.</div>		
SECTION 7. Handling and storage		
<div>7.1. Precautions for safe handling</div> <div>Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.</div> <div>7.2. Conditions for safe storage, including any incompatibilities</div> <div>Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.</div> <div>7.3. Specific end use(s)</div> <div>Information not available</div>		

## SECTION 8. Exposure controls/personal protection

## 8.1. Control parameters

## Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

## (2-methoxymethylethoxy)propanol

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	310	50	310	50	
MAK	DEU	310	50	310	50	
VLA	ESP	308	50			SKIN
VLEP	FRA	308	50			SKIN
VLEP	ITA	308	50			SKIN
NDS/NDSch	POL	240		480		SKIN
WEL	GBR	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH			50			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	19	mg/l
Normal value in marine water	1,9	mg/l
Normal value for fresh water sediment	70,2	mg/kg
Normal value for marine water sediment	7,02	mg/kg
Normal value for water, intermittent release	190	mg/l
Normal value of STP microorganisms	4168	mg/l
Normal value for the terrestrial compartment	2,74	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers		Acute	Chronic	Chronic
	Acute	Acute	Chronic	Chronic			
	local	systemic	local	systemic	local	systemic	systemic
Oral			VND	36 mg/kg bw/d			
Inhalation			VND	37,2 mg/m3		VND	308 mg/m3
Skin			VND	121 mg/kg bw/d		VND	283 mg/kg bw/d

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

**Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)****Predicted no-effect concentration - PNEC**

Normal value in fresh water	3,39	µg/l
Normal value in marine water	3,39	µg/l
Normal value for fresh water sediment	27	µg/kg
Normal value for marine water sediment	27	µg/kg
Normal value of STP microorganisms	230	µg/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		110 µg/kg bw/d		90 µg/kg bw/d				
Inhalation	40 µg/m3	NPI	20 µg/m3	NPI	40 µg/m3	NPI	20 µg/m3	NPI
Skin		NPI	NPI	NPI		NPI	NPI	NPI

**1,2-benzisothiazol-3(2H)-one****Predicted no-effect concentration - PNEC**

Normal value in fresh water	4,03	µg/l
Normal value in marine water	403	ng/l
Normal value for fresh water sediment	49,9	µg/kg
Normal value for marine water sediment	4,99	µg/kg
Normal value of STP microorganisms	1,03	mg/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,2 mg/m3				6,81 mg/m3
Skin				345 µg/kg bw/d				966 µg/kg bw/d

**2-methyl-2H-isothiazol-3-one****Predicted no-effect concentration - PNEC**

Normal value in fresh water	3,39	µg/l
Normal value in marine water	3,39	µg/l
Normal value of STP microorganisms	230	µg/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		53 µg/kg bw/d		27 µg/kg bw/d				
Inhalation	43 µg/m3	NPI	21 µg/m3	NPI	43 µg/m3	NPI	21 µg/m3	NPI
Skin	NPI	NPI	NPI	NPI		NPI	NPI	NPI

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SECTION 8. Exposure controls/personal protection** ... / >>**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	pasty liquid	
Colour	White and the colour chart shades	
Odour	Feeble	
Melting point / freezing point	not available	
Initial boiling point	> 100 °C	
Flammability	not flammable	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	> 60 °C	
Auto-ignition temperature	not applicable	
Decomposition temperature	not available	
pH	8-10	
Kinematic viscosity	not available	
Dynamic viscosity	5000 cps	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,2	
Relative vapour density	not available	
Particle characteristics	not applicable	

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Information not available

**9.2.2. Other safety characteristics**

VOC (Directive 2004/42/EC) :	5,38 % - 64,54	g/litre
VOC (volatile carbon)	2,47 % - 29,62	g/litre
Explosive properties	not applicable	
Oxidising properties	not applicable	

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

(2-methoxymethylethoxy)propanol

Forms peroxides with: air.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

(2-methoxymethylethoxy)propanol

May react violently with: strong oxidising agents.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

(2-methoxymethylethoxy)propanol

Avoid exposure to: sources of heat. Possibility of explosion.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

Information not available

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

(2-methoxymethylethoxy)propanol

LD50 (Dermal):

9510 mg/kg rabbit

LD50 (Oral):

> 5000 mg/kg rat

LC50 (Inhalation vapours):

275 mg/l/7h rat

**SECTION 11. Toxicological information** ... / >>

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LD50 (Dermal): 1008 mg/kg bw (rat)  
STA (Dermal): 50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): > 64 mg/kg bw 64-561 (rat)

LC50 (Inhalation vapours): > 171 mg/m<sup>3</sup> 171-2360 (rat)

1,2-benzisothiazol-3(2H)-one

LD50 (Dermal): 2000 mg/kg bw (rat)

LD50 (Oral): > 490 mg/kg bw 490-670 (rat)

2-methyl-2H-isothiazol-3-one

LC50 (Inhalation mists/powders): 0,1 mg/l/4h ratto rif.oecd guideline 403

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction.

Contains:

2-methyl-2H-isothiazol-3-one

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**



**SECTION 12. Ecological information** ... / >>

(2-methoxymethylethoxy)propanol

LC50 - for Fish	> 1000 mg/l/96h <i>Poecilia reticulata</i>
EC50 - for Crustacea	1919 mg/l/48h
EC50 - for Algae / Aquatic Plants	6999 mg/l/72h <i>Skeletonema costatum</i>

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50 - for Fish	> 190 µg/l 190-330
EC50 - for Crustacea	> 7 µg/l 7-160
EC50 - for Algae / Aquatic Plants	> 6,3 µg/l 6,3-27,3
Chronic NOEC for Fish	46,4 µg/l 35 days
Chronic NOEC for Crustacea	> 111 µg/l 11.1-1050

1,2-benzisothiazol-3(2H)-one

LC50 - for Fish	> 2,15 mg/l 2,15-22
EC50 - for Crustacea	> 2,9 mg/l 2,9-2,94
EC50 - for Algae / Aquatic Plants	> 70 µg/l 70-150
Chronic NOEC for Algae / Aquatic Plants	> 40,3 µg/l 40-55

2-methyl-2H-isothiazol-3-one

LC50 - for Fish	> 4,77 mg/l 4,77-6
EC50 - for Crustacea	1,6 mg/l
Chronic NOEC for Crustacea	> 44,2 µg/l 44,2-550 (21 days)

**12.2. Persistence and degradability**

(2-methoxymethylethoxy)propanol

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rapidly degradable

1,2-benzisothiazol-3(2H)-one

Rapidly degradable

2-methyl-2H-isothiazol-3-one

Rapidly degradable

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

#### 14.2. UN proper shipping name

not applicable

### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group

not applicable

### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

### Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0.1%.

Substances subject to authorisation (Annex XIV REACH)  
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:  
None

Substances subject to the Rotterdam Convention:  
None

Substances subject to the Stockholm Convention:  
None

Healthcare controls	Information not available
---------------------	---------------------------

VOC (Directive 2004/42/EC) :

**SECTION 15. Regulatory information ... / >>**

Interior / exterior trim varnishes and woodstains, including opaque woodstains.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 2</b>	Acute toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>H310</b>	Fatal in contact with skin.
<b>H330</b>	Fatal if inhaled.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>EUH071</b>	Corrosive to the respiratory tract.
<b>EUH210</b>	Safety data sheet available on request.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

## SECTION 16. Other information ... / &gt;&gt;

- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.